

2009 RACE TIRE SPECIFICATIONS

Hoosier[®]

RACING TIRE



SINCE 1957

Hoosier[®]

RACING TIRE

"TIRES DESIGNED FOR CHAMPIONS"[®]

Visit Your Local Hoosier Tire Distributor To See the NEW 2009 High Performance Racing Tires and Apparel Line Up!



Racing has been a part of our lives for over 50 years! Watching Americans come to embrace the excitement of the track – while experiencing the rise of the sport to the forefront, has been a thrill and an honor we feel fortunate to have been a part of.

We proudly present our high performance racing tires and our apparel and accessories catalog in hopes that these quality products will help you show winning Hoosier spirit everywhere you go!

On behalf of the Hoosier Racing family, thanks for your support and enthusiasm.

Bob & Joyce Newton

Contact Your Hoosier Tire Distributor Today!

TABLE OF CONTENTS

LEAD #	TIRE	PAGE #
	Tread Patterns	2-3
39/40	ARCA	4
10	S.T.A.R.T. TIRES	4
13	Midget Asphalt	4
08/10/37	Late Model and Entry Level Asphalt.....	5
41	Little Car Asphalt/Mini-Cup.....	5
08/09	Modified/Supers/Sprint/Silver Crown Asphalt.....	6
12	Oval Track D.O.T. Dirt	6
36	Late Model/E-Mod/Street Stock Dirt	7-8
14	Eastern Modified/358/Sportsman Dirt.....	8
31/38	Wing Sprint Dirt	9
31	Non-Wing Sprint Dirt/Silver Crown Short Track Dirt.....	9
31	Silver Crown Dirt/Mile Tracks.....	10
35	Midget Dirt/Mini Sprint	10
42	Modified Midget/Micro Sprint Dirt/Jr. Sprint.....	10
11	Dirt Oval Karting.....	11
11	Treaded Kart	11
15	Asphalt Oval Karting.....	11
15	Asphalt Quarter Midget	11
11	Dirt Quarter Midget.....	11
22	Sprint/Road Race Kart/Super Kart	12
16	ATV	12
20	Koni Challenge	12
17	Quick Time D.O.T.....	12
17	Quick Time Pro D.O.T.....	13
17	D.O.T. Drag Radials.....	13
18	JR Dragster.....	13
28	Racing Tubes & Liner	13
18	Drag Racing	14-15
43	Road Racing Slicks – Bias	15-16
43	Road Racing Slicks – Radial.....	16
44	Road Racing Wets – Bias.....	16
46	Road Racing Wets – Radial	17
45	Sports Car D.O.T. – Bias	17
46/44	Vintage & Historic.....	17
46	Sports Car D.O.T. – Radial.....	18
46	Sports Car D.O.T. – Radial Wet	19
19	Pro Street D.O.T. – Radial.....	19
	NO WARRANTY POLICY & WARNINGS	20
	DIRECTION OF ROTATION/MOUNTING	
	INSTRUCTIONS	Inside Back Cover
	Hoosier Racing Tire Distributors	Back Cover

SEE WARNINGS STARTING ON PAGE 20

Tire rule spec tires may not be listed in this catalog. Please contact local distributor for further information.

REV. 3/09

TREAD PATTERNS

TIRE TREADS

TIRE TREADS

<p>DRAGSTER FRONT</p>  <p>A</p>	<p>DRAG FRONT</p>  <p>B</p>	<p>DRAG SLICK</p>  <p>C</p>	<p>QUICK TIME PRO</p>  <p>D</p>
<p>RACING D.O.T. RADIAL</p>  <p>E</p>	<p>KONI</p>  <p>F</p>	<p>VINTAGE</p>  <p>G</p>	<p>STREET TREAD</p>  <p>H</p>
<p>ROAD RACING WET</p>  <p>I</p>	<p>D.O.T. RADIAL WET</p>  <p>J</p>	<p>WRS-2</p>  <p>K</p>	<p>SUPER CHAIN LINK</p>  <p>L</p>
<p>RIB DIRT</p>  <p>M</p>	<p>IMCA</p>  <p>N</p>	<p>CROSSBLOCK</p>  <p>O</p>	<p>LARGE CROSSBLOCK</p>  <p>P</p>
<p>SMALL CROSSBLOCK</p>  <p>Q</p>	<p>LARGE STAGGER BLOCK</p>  <p>R</p>	<p>CHECKERBOARD</p>  <p>S</p>	<p>LARGE CHECKERBOARD</p>  <p>T</p>

TREAD PATTERNS

<p>ANGLE BLOCK</p>  <p>U</p>	<p>DIRT BOZZ STYLE</p>  <p>V</p>	<p>STAGGER BLOCK</p>  <p>W</p>	<p>MICRO FRONT</p>  <p>X</p>
<p>MIDGET FRONT</p>  <p>Y</p>	<p>TREADED KART CROSSBLOCK</p>  <p>Z</p>	<p>TREADED KART ANGLE BLOCK</p>  <p>aa</p>	<p>PRO STREET</p>  <p>bb</p>
<p>SLICK</p>  <p>cc</p>	<p>ATV KNOBBY</p>  <p>dd</p>	<p>TRI-TRAC</p>  <p>ee</p>	<p>ATV</p>  <p>ff</p>
<p>ATV FRONT - HP</p>  <p>gg</p>	<p>ATV FRONT - LS</p>  <p>hh</p>		

TIRE TREADS

TIRE TREADS

Hoosier[®]

RACING TIRE

"TIRES DESIGNED FOR CHAMPIONS"®

ARCA

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
40310	11.0/88.015 Bias Dirt	L	11.0"	28.0"	88.0"	9.5"	9.5"	13.5"	D45L, D70R (Dirt Track)
39100	11.0/28.0R-15 Radial L	cc	10.7"	27.8"	87.3"	9.5"	9.5"	12.75"	25 (Short Track Radial -L)
39200	11.0/28.0R-15 Radial R	cc	10.7"	28.2"	88.6"	9.5"	9.5"	12.75"	40 (Short Track Radial -R)
*	12.0/28.0R-15 Radial L	cc	12.0"	27.8"	87.3"	9.5"	9.5"	13.2"	Speedway L
*	12.0/28.0R-15 Radial L	cc	12.0"	28.0"	87.75"	9.5"	9.5"	13.2"	Talladega / Daytona L
*	12.0/28.0R-15 Radial R	cc	12.0"	28.2"	88.6"	9.5"	9.5"	13.2"	Speedway Right

* DETERMINED BY HOOSIER RACING TIRE CORP. PRIOR TO THE EVENT

S.T.A.R.T. TIRES

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
10400	23.0/ 7.0-13	H	7.0"	23.0"	72.2"	6"	6"	8.6"	790
10405	23.0/ 7.0-14	H	7.0"	23.0"	72.2"	6"	6"	8.6"	790
10408	24.0/ 7.0-14	H	7.0"	24.0"	75.0"	6"	6"	9.1"	790
10410	26.5/ 7.0-15	H	7.0"	26.4"	83.0"	6"	6"	9.1"	790
10415	27.0/ 7.0-15	H	7.0"	27.0"	85.0"	6"	6"	9.2"	790
10420	26.5/ 8.0-15	H	8.0"	26.5"	82.1"	8"	8"	10.2"	880, 890
10425	27.5/ 8.0-15	H	8.0"	27.5"	85.3"	8"	8"	10.7"	880, 890
10499	26.5/ 8.0-15	cc	8.0"	26.8"	84.0"	8"	8"	11.5"	950
10500	26.5/ 8.0-15	cc	8.0"	26.8"	84.0"	8"	8"	11.5"	980
10504	27.5/ 8.0-15	cc	8.0"	27.3"	86.0"	8"	8"	11.4"	960
10505	27.5/ 8.0-15	cc	8.0"	27.3"	86.0"	8"	8"	11.4"	980
08710	13.0/26.0-15	cc	13.0"	26.0"	81.5"	15"	15"	16.4"	1320
08720	13.0/27.0-15	cc	13.0"	26.8"	84.0"	15"	15"	16.4"	1330

MIDGET ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
13109	7.0/20.5-13	cc	7.0"	20.5"	65.0"	8"	8"	8.6"	MG4, MG5, MG6, 600
13110	7.0/20.5-13	cc	7.0"	20.5"	66.0"	8"	8"	8.6"	MG7, MG8
13110700	7.0/20.5-13 700	cc	7.0"	20.5"	66.0"	8"	8"	8.6"	700
13115BG06	7.0/20.5-13 BG2006	cc	7.0"	20.5"	66.0"	8"	8"	8.6"	BG2006
13195500	10.0/22.0-13 500	cc	9.0"	22.0"	69.0"	8"	8"	11.2"	500 FOCUS
13195FOCUS	10.0/22.0-13 FOCUS	cc	9.0"	22.0"	69.0"	8"	8"	11.2"	500 FOCUS
13195	10.0/22.0-13	cc	9.0"	22.0"	68.0"	8"	8"	11.2"	500 FOCUS
13196	10.0/22.5-13	cc	10.0"	22.5"	69.0"	8"	8"	11.2"	MG5
13205	10.0/23.0-13	cc	10.0"	23.0"	70.0"	8"	8"	11.6"	MG5
13206	10.0/23.0-13	cc	10.0"	23.0"	71.0"	8"	8"	11.6"	MG6
13210760	10.0/23.5-13 760	cc	10.0"	23.5"	73.0"	10"	10"	11.6"	760
13210FOC-B	10.0/23.5-13 FOC-B	cc	10.0"	23.5"	73.0"	10"	10"	11.6"	FOCUS B
13220	12.0/23.5-13	cc	12.0"	23.5"	74.0"	10-12"	10"	13.5"	MG7.3
13240	12.0/23.5-13	cc	12.0"	23.5"	74.0"	10-12"	10"	13.5"	MG7
13246	12.0/23.5-13	cc	12.0"	23.5"	74.0"	10"	10"	13.5"	MG7.8
13248	12.0/23.5-13	cc	12.0"	23.5"	74.0"	10"	10"	13.5"	MG8

SOFT ————— MG4 MG5 MG6 MG7 MG7.3 MG7.8 MG8 FIRM

LATE MODEL & ENTRY LEVEL ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	HOOSIER SPORTSMAN	HOOSIER COMANCHE
ENTRY LEVEL										
									FIRM	X-FIRM
10060	22.5/ 7.0-13	H	7.0"	22.5"	70.7"	6"	6"	8.6"	X	
10070	23.0/ 7.0-13	H	7.0"	23.0"	72.2"	6"	6"	8.6"	X	
10075	23.0/ 7.0-14	H	7.0"	23.0"	72.2"	6"	6"	8.6"	X	
10080	23.5/ 7.0-13	H	7.0"	24.0"	75.0"	6"	6"	9.1"	X	
10090	24.0/ 7.0-14	H	7.0"	24.0"	75.0"	6"	6"	9.1"		X
10204	26.5/ 7.0-15	H	7.0"	26.4"	83.0"	6"	6"	9.1"		X
10206	27.0/ 7.0-15	H	7.0"	27.0"	85.0"	6"	6"	9.2"		X
10208	27.5/ 7.0-15	H	7.0"	27.4"	86.0"	6"	6"	9.5"		X
10220	26.5/ 8.0-15	H	8.0"	26.5"	82.1"	8"	8"	10.2"		X
10230	27.5/ 8.0-15	H	8.0"	27.5"	85.3"	8"	8"	10.7"		X
10295	8.0/26.5-15	H	9.0"	26.5"	83.2"	8"	8"	11.0"	970	
10300	8.0/26.5-15	H	9.0"	27.0"	84.0"	8"	8"	11.0"	970	
10350	8.0/27.0-15	H	9.0"	27.5"	86.3"	8"	8"	11.0"	970	
LATE MODEL / MODS										
10050	8.0/23.0-13	cc	8.0"	23.5"	73.8"	8"	8"	10.2"	F60, Sportsman, TUSA	
10051	8.0/23.0-13 SH	cc	8.0"	23.0"	72.5"	8"	8"	10.2"	F60, Sportsman, TUSA	
10144	10.0/27.0-15 SX	cc	10.0"	26.5"	83.0"	10"	10"	13.2"	1055, 1058	
10160	10.0/27.0-15 SH	cc	10.0"	27.0"	84.8"	10"	10"	13.2"	1070	
10170	10.0/27.0-15	cc	10.0"	27.5"	86.0"	10"	10"	13.2"	1070	
10172	10.0/27.0-15	cc	10.0"	27.5"	86.0"	10"	10"	13.2"	1055, 1058	
10175	27.0/10.0-15 SX	cc	10.0"	26.5"	83.0"	10"	10"	13.2"	2040	
10177	27.0/10.0-15 SH	cc	10.0"	27.0"	84.8"	10"	10"	13.2"	2045, (2060, 10178)	
10179	27.0/10.0-15	cc	10.0"	27.5"	86.0"	10"	10"	13.2"	2040, 2045, (2070, 10180)	
10186	27.0/ 8.0-15 SX	cc	8.0"	26.8"	84.0"	8"	8"	11.5"	2035, 2040	
10188	27.0/ 8.0-15 MED	cc	8.0"	27.3"	86.0"	8"	8"	11.4"	2040, 2070	
10700	27.0/10.0-15 SX	cc	10.0"	26.8"	84.0"	10"	10"	13.2"	3025, 3035	
10720	27.0/10.0-15	cc	10.0"	27.3"	86.5"	10"	10"	13.2"	3035, 3045	
10900	27.0/10.0-15	cc	10.0"	27.0"	84.0"	10"	10"	13.2"	ASALMS35	
10920	27.5/10.0-15	cc	10.0"	27.5"	85.5"	10"	10"	13.2"	ASALMS45	
37130	8.0/27.0-15 L	cc	8.0"	26.8"	84.0"	8"	8"	11.5"	F45, F53, F75	
37139	8.0/27.0-15 MED	cc	8.0"	27.0"	85.0"	8"	8"	11.2"	F53, F75	
37140	8.0/27.0-15	cc	8.0"	27.3"	86.0"	8"	8"	11.4"	F53, F75	
37160	10.0/23.0-13 SH	cc	10.0"	22.4"	70.5"	10"	10"	12.5"	F15, F35	
37170	10.0/23.0-13	cc	10.0"	23.0"	72.0"	10"	10"	12.5"	F15, F35, F45	
37181	10.0/27.0-15 SX	cc	10.0"	26.8"	84.0"	10"	10"	13.2"	F45	
37190	10.0/27.0-15	cc	10.0"	27.3"	86.5"	10"	10"	13.2"	F45, (F56 37188)	
08600	27.0/10.0-15 SX	cc	10.0"	26.5"	83.0"	10"	10"	13.2"	1030, 1040	
08625	27.0/10.5-15 MED	cc	10.0"	27.0"	85.5"	10"	10"	13.2"	1030	
08650	27.0/10.0-15	cc	10.0"	27.5"	86.0"	10"	10"	13.2"	1040, 1050, 1057	
087101320	13.0/26.0-15 1320	cc	13.0"	26.0"	80.5"	15"	15"	16.2"	1320	
087201330	13.0/27.0-15 1330	cc	13.0"	27.0"	83.0"	15"	15"	16.2"	1330	

OVAL TRACK ASPHALT

OVAL TRACK ASPHALT

LITTLE CAR ASPHALT / MINI-CUP

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
41100	6.0/18.0-10	cc	6.0"	18.0"	56-57"	6-7"	7"	8.5"	LC0, LC3
41120	8.0/18.0-10	cc	8.0"	18.0"	56-57"	7-8"	8"	9.8"	LC3
41130	10.0/19.0-10	cc	10.0"	19.0"	60.0"	10"	10"	12.2"	LC3, LC5
MINI-CUP									
41149	15.0/ 7.0-8 SH	cc	6.25"	15.37"	48.25"		8.0"	7.5"	MC780
41150	15.0/ 7.0-8	cc	6.25"	15.75"	49.5"		8.0"	7.5"	MC780
SOFT	LC0			LC3		LC5		MC780	FIRM

MODIFIED/SUPERS/SPRINT ASPHALT

OVAL TRACK ASPHALT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
09110	10.0/25.0-15	cc	10.0"	25.0"	79.0"	10"	10"	12.0"	M45
09120	11.0/24.0-15	cc	11.0"	24.0"	76.0"	10"	10"	13.0"	M10, 2010, 2015
09121	11.0/24.0-15	cc	11.0"	24.0"	76.0"	12"	12"	13.0"	M30, 2030
09125	11.0/24.5-15	cc	11.0"	24.5"	77.5"	10"	10"	12.5"	M45, M50, M60, 2045, 2050
09130	12.0/25.0-15	cc	12.0"	25.0"	78.0"	10-12"	12"	14.5"	M45, 2045
09142	13.0/25.0-15	cc	13.0"	25.0"	78.0"	13-14"	13"	15.0"	2045
08400	25.5/13.0-15	cc	13.0"	25.5"	80.5"	14-15"	15"	16.4"	2020, M30
08410	26.0/13.0-15	cc	13.0"	26.0"	81.5"	14-15"	15"	16.4"	M20, M30, M45
08420	27.0/13.0-15	cc	13.0"	26.8"	84.0"	15"	15"	16.4"	M30
08422	27.0/13.0-15	cc	13.0"	26.8"	84.0"	15"	15"	16.4"	M45
09193	26.5/13.0-15 (SC1)	cc	13.0"	26.5"	82.5"	14"	14"	16.4"	M30
09194	27.0/13.0-15 (SC1)	cc	13.0"	27.0"	83.0"	14"	14"	16.4"	M30
09180	15.0/25.0-15	cc	15.0"	25.0"	79.0"	15-16"	15"	16.4"	M30
09200	17.0/28.0-15	cc	17.0"	27.7"	86.5"	18"	18"	20.0"	2045
09204	17.0/28.0-15 (SC1)	cc	17.0"	27.7"	86.5"	18"	18"	20.0"	M50
09208	17.0/28.0-15	cc	17.0"	27.7"	86.5"	18"	18"	20.0"	2048
09209	17.0/28.0-15 (SC1)	cc	17.0"	27.7"	86.5"	18"	18"	20.0"	M55

SOFT _____ FIRM

M10 2010 2015 M20 2020 M30 2030 M45 2045 2048 M50 2050 M55

OVAL TRACK D.O.T. DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
12100	P195/65D-13	V	7.0"	23.3"	73.0"	6-7"	6"	8.5"	MED
12130	P205/60D-13	V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	MED
12150	P215/60D-13	V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	SOFT MED
12160	P225/60D-15	V	8.0"	23.6"	74.5"	7-8"	7"	9.7"	MED
12170	P235/60D-13	V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	SOFT MED
12322	P245/60D-15	V	8.0"	26.0"	84.0"	8-9"	8"	10.6"	SOFT MED
12330	P255/60D-15	V	8.0"	27.0"	86.0"	8-9"	8"	10.7"	SOFT MED
12340	P265/60D-15	V	8.0"	28.0"	88.0"	8-9"	8"	11.1"	SOFT MED
12352	P275/60D-15	V	10.0"	28.0"	88.0"	10-11"	10"	12.6"	MED
12360	P285/60D-15	V	10.0"	28.5"	90.0"	10-11"	10"	12.8"	SOFT MED
12390	P305/60D-15	V	10.0"	29.0"	92.0"	10-11"	10"	13.6"	SOFT MED

NOTE: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

LATE MODEL / E-MOD / STREET STOCK DIRT

OVAL TRACK DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
SPEC									
36019	G60-15	N	8.5"	25.5"	81.0"	8"	8"	10.75"	IMCA
36020	G60-15	N	8.5"	26.0"	82.0"	8"	8"	10.75"	IMCA
36040	23.0/7.0-13	L	7.0"	23.3"	73.0"	7-8"	7"	9.0"	RC3
36050	22.5/8.0-13	L	8.0"	22.6"	71.0"	7-8"	7"	9.1"	RC1, RC3, RC4
36055	23.0/8.0-13	L	8.0"	23.3"	73.0"	7-8"	7"	9.3"	RC0, RC1, RC3, RC4
36103	8.0/26.5-15	L	8.0"	26.5"	82.0"	8-9"	8"	10.5"	500, IMCA 500
36105	8.0/27.0-15	L	8.0"	27.0"	84.0"	8-9"	8"	10.5"	500, IMCA 500
36108	10.0/27.0-15	L	10.0"	27.0"	84.0"	10-11"	10"	12.5"	500
36125	8.0/84.0-15	L	8.0"	26.0"	84.0"	8-9"	8"	11.0"	D30
36135	8.0/87.0-15	L	8.0"	27.7"	87.0"	8-9"	8"	11.3"	D30
36208	26.5/8.0-15	L	8.0"	26.5"	83.2"	8-9"	8"	11.0"	D40
36212	27.5/8.0-15	L	8.0"	27.5"	86.2"	8-9"	8"	11.2"	A40, H40, WSH40
36213	27.5/8.0-15	L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	D40
36215	26.5/8.0-15	L	8.0"	26.5"	83.2"	8-9"	8"	11.0"	RC4, A40, WSH40
36216	27.5/8.0-15	L	8.0"	27.5"	86.3"	8-9"	8"	11.2"	RC4
36220	27.0/10.5-15	L	10.5"	27.0"	86.0"	10-12"	10"	13.0"	RC3
36226	27.5/11.0-15	L	11.0"	27.0"	86.0"	10-12"	10"	13.0"	IMCA
36239	28.0/11.0-15	L	11.0"	28.0"	88.0"	10-12"	10"	13.0"	IMCA
36240	28.0/10.5-15	L	10.5"	28.0"	88.0"	10-12"	10"	13.0"	RC1, RC3, RC4
36310	29.0/10.5-15	L	10.5"	29.0"	91.0"	10-12"	10"	13.5"	RC1, RC3, RC4, RC6
36316	29.0/11.0-15	L	11.0"	29.0"	91.0"	10-12"	10"	13.5"	IMCA
36415	UMP LM9011	M	11.0"	28.5"	90.0"	12-14"	14"	14.25"	M20, M40
36430	UMP LM9211	M	11.0"	29.0"	92.0"	12-14"	14"	14.5"	M20, M30, M40
36610	88.0/11.0-15	W	11.0"	28.0"	88.0"	12-14"	12"	15.5"	D11, D15, D21, D28, D35, D45, D55
36612	88.0/11.0-15	K	11.0"	28.0"	88.0"	12-14"	12"	15.25"	WRS-2
36613	88.0/11.0-15 WISSOTA	K	11.0"	28.0"	88.0"	12-14"	12"	15.25"	WISSOTA WRS-2
36617	UMP LM8811	P	11.0"	28.0"	87.5"	12-14"	14"	14.25"	M10, M20, M30, M40
36620	90.0/11.0-15	W	11.0"	28.5"	90.0"	12-14"	12"	15.5"	D11, D15, D21, D28, D35, D45, D55
36622	90.0/11.0-15	K	11.0"	28.5"	90.0"	12-14"	12"	15.25"	WRS-2
36623	90.0/11.0-15 WISSOTA	K	11.0"	28.5"	90.0"	12-14"	12"	15.25"	WISSOTA WRS-2
36627	UMP LM9011	P	11.0"	28.5"	88.0"	12-14"	14"	14.25"	M10, M20, M30, M40
36629	92.0/11.0-15 WISSOTA	W	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WISSOTA WRS
36630	92.0/11.0-15	W	11.0"	29.0"	92.0"	12-14"	12"	15.5"	D11, D15, D21, D28, D35, D45, D55
36631	92.0/11.0-15	W	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WRS
36632	92.0/11.0-15	K	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WRS-2
36633	92.0/11.0-15 WISSOTA	K	11.0"	29.0"	92.0"	12-14"	12"	15.5"	WISSOTA WRS-2
36637	UMP LM9211	P	11.0"	29.0"	92.0"	12-14"	14"	14.5"	M10, M20, M30, M40
36860	265/60-15	V	8.0"	28.0"	88.0"	8-9"	8"	11.1"	Soft
36935	205/60-13	V	8.0"	22.6"	71.0"	7-8"	7"	9.1"	TUSA Soft, TUSA
36940	215/60-13	V	8.0"	23.3"	73.0"	7-8"	7"	9.3"	TUSA Soft, TUSA Medium, TUSA
36945	235/60-13	V	8.0"	23.8"	75.0"	7-8"	7"	10.2"	TUSA Soft, TUSA Medium, TUSA
PREMIUM SPEC									
36605	28.5/11.0-15	U	11.0"	28.5"	90.5"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36606	28.5/11.0-15	U	11.0"	28.5"	90.5"	12-14"	14"	14.25"	CR21, CR55, USA21, USA55
36615	88.0/11.0-15	P	11.0"	28.0"	86.5"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36616	88.0/11.0-15	P	11.0"	28.0"	86.5"	12-14"	14"	14.25"	CR21, CR55, USA21, USA55
36625	90.0/11.0-15	P	11.0"	28.5"	88.0"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36626	90.0/11.0-15	P	11.0"	28.5"	88.0"	12-14"	14"	14.25"	CR21, CR55, USA21, USA55
36635	92.0/11.0-15	P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	1200, 1300, 1350, 1600
36636	92.0/11.0-15	P	11.0"	29.0"	92.0"	12-14"	14"	14.25"	CR21, CR55, USA21, USA55

LATE MODEL / E-MOD / STREET STOCK DIRT CON'T.

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
OPEN COMPETITION									
36143	26.0/8.0-15	L	8.0"	26.0"	82.0"	8-9"	8"	11.0"	Soft, Medium
36149	26.5/8.0-15	L	8.0"	26.5"	84.0"	8-9"	8"	11.2"	Soft, Medium, Hard
36155	27.5/8.0-15	L	8.0"	27.5"	86.0"	8-9"	8"	11.2"	Soft, Medium, Hard
36421	28.5/11.0-15	M	11.0"	28.5"	89.5"	12-14"	14"	14.25"	1200, 1300, 1350, 1400, 1425, 1450, 1600
36422	28.5/11.0-15	P	11.0"	28.5"	88.0"	12-14"	14"	14.25"	1100
36431	29.0/11.0-15	M	11.0"	29.0"	92.0"	12-14"	14"	14.5"	1200, 1300, 1350, 1400, 1425, 1450, 1600
36727	28.5/11.0-15 C4000	U	11.0"	28.5"	90.5"	12-14"	14"	14.25"	1100, 1200, 1300, 1350, 1400, 1425, 1450, 1600, 2400
36733	11.0/86.0-15 C2150	P	11.0"	28.0"	87.5"	12-14"	14"	16.25"	1100, 1200, 1300, 1350
36743	11.0/88.0-15 C2150	P	11.0"	28.0"	88.5"	12-14"	14"	16.25"	1100
36747	11.0/88.0-15 C4000	P	11.0"	28.0"	88.5"	12-14"	14"	16.25"	1200, 1300, 1350, 1400, 1425, 1450, 1600, 2400
36781	29.0/11.0-15	P	11.0"	29.5"	92.0"	12-14"	14"	14.5"	1100
36785	11.0/92.0-15	P	11.0"	29.5"	92.0"	12-14"	14"	16.5"	1100
36787	29.0/11.0-15	P	11.0"	29.5"	92.0"	12-14"	14"	14.5"	1200, 1300, 1350, 1400, 1425, 1450, 1600, 2400, 2500
36357	29.0/11.0-15	P	11.0"	29.5"	92.0"	12-14"	14"	16.0"	2700

	D11		D40 D15	CR21 D21 1350		D28 2400	D35	A40 D45 1450		USA55 CR55	WRS-2 D55 WRS	H40 IMCA 2700	
SOFT	1100	1200	1300	TUSA Soft	USA21	TUSA Med	1400	1425	TUSA	1500	HARD	1600	FIRM
	RC0			RC1 SOFT			RC3 MED		RC4				
	M10			M20				M30			M40		

EASTERN MODIFIED / 358 / SPORTSMAN DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
14131	11.0/82.0-15SH	L	10.5"	25.5"	80.5"	10-12"	10"	12.0"	D200, D300, D400
14133	11.0/82.0-15	L	10.5"	26.0"	82.0"	10-12"	10"	12.0"	D300, D400
14135	11.0/87.0-15	L	11.0"	27.2"	85.5"	10-12"	12"	14.2"	M45, D50
14143	11.0/90.0-15SH	L	11.0"	28.0"	88.5"	10-12"	12"	14.2"	M45, D50
14145	11.0/90.0-15	L	11.0"	29.0"	90.5"	10-12"	12"	14.5"	M45, D60
14151	13.0/82.0-15	L	13.0"	26.3"	82.0"	12-14"	13"	14.0"	D200, D300, D400, D500
14178	13.0/87.0-15	L	13.0"	27.5"	86.0"	12-14"	14"	16.2"	D200, D300, D400,
14190	13.0/89.0-15	L	13.0"	28.0"	88.0"	12-14"	14"	16.2"	D200, D300, D400,
14225	13.0/92.0-15	L	13.0"	29.0"	91.5"	12-14"	14"	16.5"	D200, D300, D400, D500
14226	13.0/92.0-15Tall	L	13.0"	29.5"	92.5"	12-14"	14"	16.5"	D200, D300, D400,

*Open competition tires to be announced

SOFT	D200	Soft D300	M45	D50	Hard D400	D60	Extra D500	FIRM
------	------	--------------	-----	-----	--------------	-----	---------------	------

NOTE: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

WING SPRINT DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
31131	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D10, D12
31132	85.0/ 8.0-15	L	8.0"	27.0"	85.0"	8"	8"	10.5"	D15, D20
31135	86.0/ 8.0-15	L	8.5"	27.0"	85.0"	8"	8"	10.7"	F25, F35
31149	88.0/15.0-15	T	15.0"	28.0"	88.0"	14-15"	15"	18.6"	D10
31159	90.0/15.0-15	T	15.0"	28.5"	90.0"	14-15"	15"	18.0"	D10, RD12
31169	92.0/15.0-15	T	15.0"	29.0"	92.0"	14-15"	15"	18.5"	D10, RD12, D12, D15
31189	94.0/15.0-15	T	15.0"	30.0"	94.0"	14-15"	15"	18.3"	RD12, D12, RD15, D15, D20
31191	94.0/15.0-15	T	15.0"	29.7"	93.5"	14-15"	15"	18.3"	D10
31209	96.0/15.0-15	T	15.0"	30.5"	96.0"	14-15"	15"	18.7"	D10, RD12, D12, RD15, D15
31242	98.0/15.0-15	T	15.0"	31.5"	98.0"	14-15"	15"	18.5"	RD12, D12
31303	105.0/18.0-15	T	18.0"	32.2"	105.0"	16-18"	18"	21.5"	D10, RD12, D12, RD15, D15, RD20, D25
38123	88.0/14.0-15	T	15.0"	28.0"	88.0"	14-15"	14"	18.0"	MED
38133	90.0/14.0-15	T	15.0"	28.5"	90.0"	14-15"	14"	18.0"	MED
38135	90.0/14.0-15	T	15.0"	28.5"	90.0"	14-15"	14"	18.0"	RC1
38143	92.0/14.0-15	T	15.0"	29.0"	92.0"	14-15"	14"	18.0"	MED, IMCA
38146	92.0/14.0-15	T	15.0"	29.0"	92.0"	14-15"	14"	18.0"	RC1
38153	94.0/14.0-15	T	15.0"	30.0"	94.0"	14-15"	14"	18.0"	MED
38156	94.0/14.0-15	T	15.0"	30.0"	94.0"	14-15"	14"	18.0"	RC1
38162	96.0/14.0-15	T	15.0"	30.5"	96.0"	14-15"	14"	18.5"	RC1, MED
38172	102.0/16.0-15	T	15.0"	32.5"	102.0"	15-17"	16"	19.3"	RC3, VRA, IMCA
38230	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	HTC
38231	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	Hard
38250	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	SC12, SCRD15, SC15, SC25

SOFT	D10	RD12	RC1 SC12 D12 F12	SCRD15 RD15	HTC SC15 D15 F35	RD20 MED	D20	DT3 RC3	SC25 D25 HARD, IMCA, VRA	FIRM
------	-----	------	---------------------------	----------------	---------------------------	-------------	-----	------------	--------------------------------	------

NON-WING SPRINT/SILVER CROWN SHORT TRACK DIRT

OVAL TRACK DIRT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
31131	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D10, D12
31132	85.0/ 8.0-15	L	8.0"	27.0"	85.0"	8"	8"	10.5"	D15, D20
31135	86.0/ 8.0-15	L	8.5"	27.0"	85.0"	8"	8"	10.7"	F25, F35
31163	90.0/14.0-15	T	15.0"	28.5"	90.0"	14"	14"	18.0"	D10
31183	92.0/14.0-15	T	15.0"	29.0"	92.0"	14"	14"	18.0"	D10
31203	94.0/14.0-15	T	15.0"	30.0"	94.0"	14"	14"	18.0"	D10
31225	96.0/14.0-15	T	15.0"	30.5"	96.0"	14"	14"	18.5"	D10, RD12
31227	96.0/14.0 W-15	T	16.0"	30.5"	97.0"	15"	15"	19.0"	RD12
31237	98.0/14.0-15	T	15.0"	31.5"	98.0"	14"	14"	18.5"	RD12, D12
31239	98.0/14.0 W-15	T	16.0"	31.5"	99.0"	15"	15"	19.0"	RD12
31247	100.0/13.0-15	S	13.2"	31.8"	101.0"	14"	14"	17.2"	D25
31249	100.0/13.0-15	S	13.2"	31.8"	100.0"	14"	14"	17.2"	RD12, D12
31256	103.0/14.0-15	T	14.5"	32.1"	101.0"	14"	14"	18.5"	RD12, D25
31305	105.0/18.0-15	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	F55
31303	105.0/18.0-15	C-2055	T	18.0"	33.2"	105.0"	16-18"	18"	D10, RD12, D12, RD15, D15, RD20, D25
38215	104.0/17.0-15	S	17.0"	33.0"	107.5"	16-18"	18"	21.0"	DT3

SOFT	D10	RD12	D12 F25	RD15	D15 F35	RD20	D20	D25, DT3	F55	FIRM
------	-----	------	------------	------	------------	------	-----	----------	-----	------

SILVER CROWN DIRT / MILE TRACKS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
DIRT ONLY									
31132	85.0/ 8.0-15	L	8.0"	27.0"	84.5"	8"	8"	10.5"	D20, F75
31247	100.0/13.0-15	S	13.2"	31.8"	100.0"	14"	14"	17.2"	D50, F55
31256	103.0/14.0-15	T	14.5"	32.1"	101.0"	14"	14"	18.5"	D50, F55
31303	105.0/18.0-15 C2055	T	18.0"	33.2"	105.0"	16-18"	18"	21.5"	F85, F95
SOFT			D12	D20	D50	F55	F75	F85	F95 FIRM

MIDGET DIRT / MINI SPRINT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
35112	68.0/ 7.0-13	Y	7.0"	21.6"	68.0"	7-8"	7"	8.5"	D12, D15, D20
35130	72.0/10.0-13	R	10.0"	23.0"	72.0"	8-10"	8"	11.7"	RD12
35140	74.0/10.0-13	Q	10.0"	23.7"	73-74"	8-10"	8"	11.7"	D10, D12
35155	76.0/10.0-13	Q	10.0"	24.2"	75-76"	8-10"	8"	12.0"	D10, RD12, D12, FOCUS, DSS
35165	78.0/10.0-13	Q	10.0"	24.8"	77-78"	8-10"	8"	12.0"	D10, RD12, D12, FOCUS, D20
35172	80.0/10.0-13	Q	10.0"	25.5"	79-80"	8-10"	8"	12.0"	RD12, D12, FOCUS
35234	82.0/12.0-13	T	12.0"	26.1"	81-82"	10-12"	10"	14.1"	RD12, SP2, SP3, SP4
35240	84.0/12.0-13	T	12.0"	26.7"	84.0"	10-12"	10"	14.1"	D10, RD12, RD15, D12, D15

SOFT ————— D10 RD12 D12 RD15 D15 SP2 D20 SP3 SP4 FIRM

MODIFIED MIDGET/MICRO SPRINT DIRT/JR. SPRINT

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
42050	57.0/ 6.0-10	X	5.8"	18.0"	57.0"	5-6"	5"	6.8"	D10, D12, D15, D20
42100	57.0/ 6.5-10	L	7.0"	18.0"	57.0"	7"	7"	8.7"	D10, D12, D15, D20, D25
42124	59.0/ 8.0-10	P	8.5"	18.5"	58.5"	8"	8"	9.5"	D10, RD12, RD15, RD20, D25
42126	59.0/10.0-10	P	10.0"	18.5"	58.5"	10"	10"	10.9"	D10, RD12, RD15, D20, D25
42130	60.0/ 7.0-10	L	7.5"	19.0"	60.0"	7"	7"	9.0"	D10, D12, D15, D20, D25
42164	61.0/ 8.0-10	P	8.2"	19.0"	60.5"	8"	8"	10.1"	D10, RD12, RD15, D20, D25
42168	61.0/10.0-10	P	10.2"	19.0"	60.5"	10"	10"	11.8"	D10, RD12, RD15, D20, D25
42170	62.0/ 8.0-10	P	8.2"	19.7"	62.0"	8"	8"	10.1"	D10, RD12, RD15, RD20
42172	62.0/10.0-10	P	10.0"	19.7"	62.0"	10"	10"	11.9"	D10, RD12, RD15, RD20
42173	63.0/ 8.0-10	P	8.2"	19.0"	63.0"	8"	8"	10.1"	RD12, RD15, RD20, D25
42183	63.0/10.0-10	P	10.0"	20.0"	63.0"	10"	10"	12.0"	D10, RD12, RD15, D20, D25
42185	64.0/ 8.0-10	P	8.2"	20.2"	64.0"	8"	8"	10.6"	RD12, RD15
42195	64.0/10.0-10	P	10.0"	20.2"	64.0"	10"	10"	12.5"	D10, RD12, RD15, D20
42225	65.0/10.0-10	O	10.0"	20.5"	65.0"	10"	10"	11.5"	D10, RD12, D12, RD15, RD20, D20, D25, D35
42229	67.0/10.0-10	O	10.0"	21.3"	67.0"	10"	10"	11.5"	RD12, D12, RD15
42237	69.0/10.0-10	O	11.0"	22.0"	69.0"	10-12"	10"	12.5"	D10, RD12, D12, RD15, D20, D25, D30, D35
42239	69.0/10.0 W-10	O	12.5"	22.0"	69-70"	10-12"	11"	14.7"	D10, RD12, D12, RD15, RD20, D20, D25, D30, NMMA, ASCS2, D35
42400	15.0/ 6.0-8	aa	6.0"	15.0"	49.0"	6"	6"	7.4"	RD20
42450	15.0/ 7.0-8	Q	7.0"	15.0"	49.0"	6"	6"	7.5"	RD20
42500	15.0/ 8.0-8	Q	8.0"	15.0"	49.5"	7"	7"	8.5"	RD20
42550	16.0/ 8.5-8	Q	8.5"	16.0"	53.5"	9"	9"	10.5"	RD20

SOFT ————— D10 RD12 D12 RD15 D15 RD20 D20 D25 D30 NMMA D35 ASCS2 FIRM

OVAL TRACK DIRT

OVAL TRACK DIRT

DIRT OVAL KARTING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
11300	10.5 x 4.5-6 C01	cc	4.5"	10.5"	32.5"	6-6.5"	6.5"	6.50"	D10, D20A, D30
11305	10.5 x 4.5-6 C02	cc	4.5"	10.5"	32.5"	6-6.5"	6.5"	6.50"	D40A, RD30
11352	10.5 x 5.5-6 NWOK	cc	5.5"	10.5"	32.5"	7.75-8.5"	8"	7.75"	D10, D20A, D30
11376	11.0 x 6.0-6 C01	cc	5.5"	10.7"	33.0"	7.75-8.5"	8.5"	7.875"	D10, D20A, D30
11380	11.0 x 6.0-6 NWOK	cc	5.5"	10.7"	33.0"	7.75-8.5"	8.5"	7.875"	D10, D20A, D30
11401	11.0 x 6.0-6 C02	cc	5.5"	10.7"	33.0"	7.75-8.5"	8.5"	7.875"	RD30, D40A, D60
11650	11.5 x 6.5-6	cc	6.25"	11.5"	34.75"	8-8.5"	8.5"	8.25"	D20A
11850	11.0 x 8.1-6 C01	cc	8.25"	11.0"	34.0"	9-10"	10"	9.875"	D10, D20A, D30
11855	11.0 x 8.1-6 C02	cc	8.25"	11.0"	34.0"	9-10"	10"	9.875"	RD30, D40A, D60
11860	11.0 x 8.1-6 NWOK	cc	8.25"	11.0"	34.0"	9-10"	10"	9.875"	D40A

TREADED KART

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
11900	11.0 x 5.5-6	aa	5.5"	11.0"	35.0"	6-6.5"	6.5"	6.5"	D10, D20A, D30
11905	11.0 x 5.5-6 NWOK	aa	5.5"	11.0"	35.0"	6-6.5"	6.5"	6.5"	D20A, D30, D40A
11940	12.0 x 8.0-6	Z	8.0"	12.0"	38.0"	9-10"	10.0"	9.75"	D10, D20A, D30
11945	12.0 x 8.0-6 CB NWOK	Z	8.0"	12.0"	38.0"	9-10"	10.0"	9.75"	D10, D20A, D30
11960	12.0 x 9.0-6	Z	9.0"	12.0"	39.0"	9-10"	10.0"	10.25"	D10, D20A, D30, D50
11965	12.0 x 9.0-6 CB NWOK	Z	9.0"	12.0"	39.0"	9-10"	10.0"	10.25"	D20A, D30, D55

ASPHALT OVAL KARTING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
15300	10.5 x 4.5-6	cc	4.5"	10.5"	33"	6"	6"	6.25"	A40
15750	11.0 x 7.1-6	cc	7.25"	11.0"	34"	9"	9"	8.875"	A40
15810	11.0 x 8.1-6	cc	8.25"	11.0"	34"	10"	10"	9.875"	A40, A40A

ASPHALT QUARTER MIDGET

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
15151	31.0/4.5-5 C02	cc	4.5"	10.0"	31"	5-6"	5"	5.5"	A30, A40A
15152	31.0/4.5-5 C02	cc	4.5"	10.0"	31"	5-6"	5"	5.5"	A30A
15171	32.0/4.5-5 C02	cc	4.5"	10.25"	32"	5-6"	5"	5.5"	A30, A30A, A40A
15301	33.0/4.5-6 C02	cc	4.5"	10.5"	33"	6-6.5"	6"	6.25"	A40A
15600	34.5/6.0-6	cc	5.75"	11.0"	34.5"	8-8.5"	8.5"	8.5"	A40A
USAC	.25 MIDGET	POSITION							
15325	33.0/5.0-6	RF	4.75"	10.5"	33.5"	6-6.5"	6"	6.25"	A35, A40AR
15650	34.5/5.5-6	RR	6.25"	11.0"	34.75"	8-8.5"	8.5"	8.25"	A35, A40A
15751	35.0/7.1-6	Wide RR	7.00"	11.0"	35"	8-9"	9.0"	8.75"	A35, A40A

DIRT QUARTER MIDGET

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
11050	31.0/4.5-5 C01	cc	4.5"	10.00"	31"	5-6"	5"	5.5"	D10, D20A
11100	32.0/4.5-5 C01	cc	4.5"	10.25"	32"	5-6"	5"	5.5"	D10, D20A
11160	33.0/4.5-6 C01	cc	4.5"	10.50"	33"	6-6.5"	6"	6.25"	D60
11175	33.0/5.5-6	cc	4.75"	10.50"	33.5"	6-6.5"	6"	7.25"	D10, D30
11225	34.5/6.5-6	cc	6.25"	11.00"	34.75"	8-8.5"	8.5"	8.25"	D10, D30
11260	35.0/7.1-6 C01	cc	7.25"	11.00"	35"	8-9.25"	8.5"	8.75"	D60

SPRINT/ROAD RACE KART/SUPER KART

KART/ATV

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
22150	4.5/10.0-5	cc	4.25"	10.0"	32"	5.0-5.5"	5.0"	5.5"	R60
22250	6.0/11.0-5	cc	5.5"	11.0"	34"	7.0-7.25"	7.0"	7.25"	R60
22350	7.1/11.0-5	cc	6.75"	11.0"	34"	8.0-8.25"	8.25"	8.50"	R60
22400	7.1/11.0-5 S	cc	6.75"	11.0"	34"	8.0-8.25"	8.25"	8.50"	R60
22700	5.0/10.5-6	cc	4.25"	10.5"	33.5"	6"	6.0"	6.75"	R60
22750	5.5/10.5-6	cc	4.50"	10.5"	34"	6"	6.0"	7.00"	R60
22855	7.1/11.0-6	cc	7.0"	11.0"	35"	8"	8.0"	8.25"	R60
22900	8.0/11.0-6	cc	7.25"	11.0"	35.5"	8.5-9"	8.5"	8.75"	R60

ATV

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS	APPLICATION
16110	18.0 X 11.0-10	ee	10.0"	18.0"	57.0"	10"	10"	11.0"	T10, T20	MX
16130	18.5 X 6.0-10	ff	6.0"	18.5"	59.0"	5"	5"	7.5"	T10	MX
16250	18.0 X 5.5-10	X	5.5"	18.0"	57-58"	5"	5"	6.6"	D10, D12	Flat Track & TT
16275	18.5 X 8.0-10	P	8.5"	18.5"	59.0"	8"	8"	9.5"	D10, RD12, D12, RD15, RD20	Flat Track & TT
16300	18.5 X 10.0-9	P	10"	18.5"	59.0"	10"	10"	10.9"	RD12, D12, RD15	Flat Track & TT
16325	18.5 X 10.0-10	P	10"	18.5"	59.0"	10"	10"	10.9"	D10, RD12, D12, RD15, RD20	Flat Track & TT
16500	20.0 X 6.0-10	gg	4.5"	20.0"	62.75"	5"	5"	5.875"	MX200	MX
16600	20.5 X 6.0-10	hh	5.0"	20.5"	63.25"	5"	5"	6.5"	MX200	MX-Front
16700	18.0 X 10.0-8	dd	8.5"	18.0"	56.5"	8"	8"	9.625"	MX100, MX200	MX
42400	15.0 X 6.0-8	aa	6.0"	15.0"	49.0"	6"	6"	7.4"	RD20	
42450	15.0 X 7.0-8	Q	7.0"	15.0"	49.0"	6"	6"	7.5"	RD20	
42500	15.0 X 8.0-8	Q	8.0"	15.0"	49.0"	7"	7"	8.5"	RD20	
42550	16.0 X 8.5-8	Q	8.5"	16.0"	53.5"	9"	9"	10.5"	RD20	

Hoosier ATV Tires are designed and manufactured for racing purposes only, within a closed course designed for organized competition. Not for recreation use.

SOFT ——— D10 RD12 D12 RD15 RD20 MX100 T10 T20 MX200 FIRM

KONI CHALLENGE SERIES

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	
*20220	225/45R15	KONI	F	KONI	8.7"	22.7"	71.4"	8.5-9"	8"	9.5"
*20230	225/45R17	KONI	F	KONI	8.7"	24.5"	76.9"	8.5-9"	8"	9.6"
*20240	245/40R17	KONI	F	KONI	9.1"	24.4"	76.7"	9-9.5"	9"	10.1"
*20245	245/45R17	KONI	F	KONI	9.4"	25.3"	79.4"	9-9.5"	9"	9.9"
*20260	275/40R17	KONI	F	KONI	10.2"	25.3"	79.5"	10-10.5"	10"	11.1"
*20270	275/35R18	KONI	F	KONI	10.2"	25.3"	79.5"	10-10.5"	10"	11.0"
*20120WET	225/45R15	KONI		KONI	8.7"	22.8"	71.5"	8.5-9"	8"	9.6"

*Not D.O.T. Approved

QUICK TIME D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
17010	P175/70D-15	L	5.6"	24.8"	78.0"	5-6"	5"	7.3"	Quick Time Frt.
17030	P275/55D-14	L	8.5"	26.1"	82.0"	6-8"	8"	10.1"	Quick Time
17050	P245/60D-15	L	8.0"	26.1"	82.0"	6-8"	8"	11.1"	Quick Time
17110	P275/60D-15	L	9.0"	27.0"	85.0"	8-10"	8"	11.8"	Quick Time
17100	P275/50D-15	L	10.0"	26.1"	82.0"	8-10"	8"	11.6"	Quick Time
17125	P295/60D-15	L	10.0"	29.0"	92.0"	8-10"	8"	12.6"	Quick Time
17120	P295/50D-15	L	10.0"	27.0"	85.0"	8-10"	8"	12.8"	Quick Time
17130	P325/50D-15	L	10.5"	27.8"	87.5"	8-10"	8"	13.1"	Quick Time
17140	31 X 16.50-15 LT	L	14.0"	30.9"	97.0"	12-14"	14"	17.8"	Quick Time
17150	31 X 18.50-15 LT	L	15.0"	30.9"	97.0"	14-15"	14"	18.3"	Quick Time
17210	33 X 22.50-15 LT	L	17.0"	33.0"	103.5"	15-16"	15"	21.1"	Quick Time

QUICK TIME PRO D.O.T.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
17411	26 X 9.50-14 LT	D	8.0"	26.1"	82.0"	6-8"	8"	10.0"	Quick Time Pro
17415	26 X 9.50-15 LT	D	8.0"	26.1"	82.0"	6-8"	8"	9.9"	Quick Time Pro
17421	26 X 11.50-15 LT	D	10.0"	26.4"	83.0"	8-10"	8"	11.5"	Quick Time Pro
17430	26 X 9.50-16 LT	D	8.0"	26.1"	82.0"	6-8"	8"	9.3"	Quick Time Pro
17500	27 X 10.50-15 LT	D	9.0"	27.0"	85.0"	8-10"	8"	10.1"	Quick Time Pro
17510	27 X 11.50-15 LT	D	10.0"	27.0"	85.0"	8-10"	8"	11.2"	Quick Time Pro
17601	28 X 11.50-15 LT	D	10.0"	28.0"	88.0"	8-10"	8"	11.2"	Quick Time Pro
17603	28 X 11.50-16 LT	D	10.0"	28.0"	88.0"	8-10"	10"	11.8"	Quick Time Pro
17606	28 X 13.50-15 LT	D	11.0"	28.0"	88.0"	10-12"	10"	12.9"	Quick Time Pro
17611	28 X 14.50-15 LT	D	12.0"	28.0"	88.0"	10-12"	10"	13.1"	Quick Time Pro
17651	28 X 14.50-16 LT	D	12.0"	28.0"	88.0"	10-12"	10"	12.9"	Quick Time Pro
17700	29 X 11.50-15 LT	D	10.0"	29.3"	92.0"	8-10"	8"	11.9"	Quick Time Pro
17705	29 X 13.50-15 LT	D	11.0"	29.3"	92.0"	10-12"	10"	13.4"	Quick Time Pro
17710	29 X 14.50-15 LT	D	12.0"	29.3"	92.0"	10-12"	10"	13.9"	Quick Time Pro
17790	31 X 13.50-15 LT	D	11.0"	30.9"	97.0"	10-12"	10"	14.1"	Quick Time Pro
17800	31 X 16.50-15 LT	D	13.0"	30.9"	97.0"	12-14"	12"	16.0"	Quick Time Pro
17810	31 X 18.50-15 LT	D	15.0"	30.9"	97.0"	14-15"	14"	17.9"	Quick Time Pro
17900	33 X 18.50-15 LT	D	15.0"	33.0"	104.0"	14-15"	14"	18.5"	Quick Time Pro
17910	33 X 22.50-15 LT	D	17.0"	33.0"	104.0"	15-16"	15"	20.0"	Quick Time Pro
17950	35 X 22.50-16 LT	D	17.0"	35.0"	110.0"	15-16"	16"	21.5"	Quick Time Pro

SOFT _____ Quick Time _____ FIRM
 Quick Time Pro _____ Quick Time Frt.

D.O.T. DRAG RADIALS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
17310	P225/50R-15	E	8.5"	23.9"	75.2"	7-9"	7"	9.3"	
17315	P275/50R-15	E	9.5"	25.7"	80.8"	8-10"	8.5"	10.8"	
17316	P295/65R-15	E	10.0"	29.6"	93.0"	8-10"	8.5"	12.0"	
17317	P275/60R-15	E	10.0"	28.0"	87.6"	8-10"	8"	11.3"	
17318	P325/50R-15	E	11.75"	27.7"	87.2"	9-11"	10"	13.2"	
17319	P315/60R-15	E	11.1"	29.7"	93.5"	9-11"	9.5"	12.8"	
17320	P225/50R-16	E	8.8"	24.9"	78.3"	7-9"	7"	9.3"	
17325	P255/50R-16	E	9.5"	26.3"	82.5"	8-10"	8"	10.5"	
17330	P275/40R-17	E	9.8"	25.7"	81.0"	9-11"	10"	11.3"	
17332	P315/35R-17	E	11.5"	25.6"	81.6"	9-11"	11"	12.6"	
17335	P335/35R-17	E	12.0"	25.9"	81.4"	11-13"	12"	13.5"	
17342	P315/30R-18	E	11.0"	26.0"	81.7"	11-12"	11"	11.7"	
17345	P335/30R-18	E	12.2"	26.2"	82.2"	12-13"	12"	13.2"	

JR DRAGSTER

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
18030	18.0/ 8.0-8	C	7.7"	17.7"	55.5"	7-8"	8"	9.9"	JR3
18040	18.0/ 10.0-8	C	9.5"	17.7"	55.5"	8-10"	8"	10.6"	JR3

RACING TUBES & LINER

ITEM NUMBER	TUBE SIZE	TREAD WIDTH
288088-15	80/ 88-15 TUBE	WILL FIT 80" TO 88" CIRC. 6" TO 11" TREAD WIDTH
2886100-15	86/100-15 TUBE	WILL FIT 86" TO 100" CIRC. 11" TO 13" TREAD WIDTH
2894106-15	94/106-15 TUBE	WILL FIT 94" TO 106" CIRC. 15" TO 19" TREAD WIDTH
32400	75/16.0-16 LINER	FOR USE WITH ITEM NUMBERS 18790, 18800, 18900

DRAG RACING

DRAG RACING

DRAG RACING

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
Drag Front									
18085	23.0/ 5.0-15	B	4.8"	23.0"	72.0"	3.5-4"	3.5"	5.8"	Drag Front
18095	24.0/ 5.0-15	B	4.8"	23.8"	75.0"	3.5-4"	3.5"	5.8"	Drag Front
18102	25.0/ 5.0-15	B	4.8"	24.8"	77.9"	3.5-4"	3.5"	5.8"	Drag Front
18105	26.0/ 4.5-15	B	4.3"	25.8"	81.0"	3.5-4"	3.5"	5.9"	Drag Front
18106	27.0/ 4.5-15	B	4.5"	27.0"	85.0"	3.5-4"	4"	7.2"	Drag Front
18107	28.0/ 4.5-15	B	4.5"	27.7"	87.0"	3.5-4"	4"	7.6"	Drag Front
18108	22.0/ 2.5-17	A	1.5"	22.0"	69.0"	2.5"	2.5"	2.7"	Dragster Front
Drive Tires - Slicks									
18060	24.5/ 8.0-13	C	7.8"	24.3"	76.0"	6-8"	7"	9.7"	D06
18110	26.0/ 8.0-15	C	8.0"	26.1"	82.0"	7-8"	8"	9.7"	D06
18115	26.0/ 8.5-15	C	9.0"	26.1"	82.0"	7-8"	8"	10.3"	C11
18120	26.0/ 9.0-15	C	9.0"	26.1"	82.0"	7-8"	8"	10.3"	D06
18131	26.0/10.0-15	C	10.0"	26.2"	82.0"	8-10"	9"	11.0"	D06
18140	28.0/ 9.0-15	C	9.0"	28.0"	88.0"	8-10"	8"	11.1"	D06
18150	28.0/10.0-15	C	10.0"	28.0"	88.0"	8-10"	8"	11.7"	D06
18153	28.0/10.0-16	C	10.0"	28.0"	88.0"	8-10"	10"	12.0"	C07
18154	10.5/28.0-15	C	10.0"	28.0"	88.0"	8-10"	10"	12.6"	C07
18155	28.0/10.5-15*	C	10.2"	28.0"	88.0"	8-10"	8"	12.0"	C07
18160	29.0/ 9.0-15	C	9.0"	29.1"	91.5"	8-10"	8"	11.4"	D06
18170	29.0/10.0-15	C	10.0"	29.1"	91.5"	8-10"	8"	11.9"	D06
18175	29.0/10.5-15 W*	C	11.0"	29.3"	92.0"	8-10"	10"	13.2"	D06
18180	29.0/11.0-15	C	11.0"	29.3"	92.0"	8-10"	10"	13.2"	D06
18190	29.0/12.0-15	C	12.0"	29.3"	92.0"	10-12"	10"	13.7"	D06
18192	29.5/10.5-15	C	11.1"	30.6"	96.0"	10-12"	10"	13.2"	D06
18193	29.5/10.5-15	C	10.5"	30.0"	94.0"	10-12"	10"	13.1"	C11
18195	29.5/11.5-15 W*	C	13.5"	30.6"	96.0"	12-14"	12"	15.2"	D06
18200	30.0/ 9.0-15	C	9.0"	30.0"	94.0"	8-10"	8"	11.8"	D05, D07
18205	30.0/10.5-15	C	10.5"	30.0"	94.0"	8-10"	10"	13.1"	D05
18209	30.0/9.0R-15 Radial***	C	9.0"	29.5"	92.5"	8-10"	8"	11.3"	C06
18210	30.0/9.0R-15 Radial	C	9.0"	29.5"	92.5"	8-10"	8"	11.3"	C07
18211	9.0/30.0R-15 Radial	C	9.0"	29.9"	94.0"	8-10"	8"	11.3"	C07
18212	9.0/30.0R-15 Radial***	C	9.0"	29.9"	94.0"	8-10"	8"	11.3"	C06
18214	30.0/10.5R-15 Radial***	C	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C06
18215	30.0/10.5R-15 Radial	C	10.5"	29.5"	92.5"	9-10"	10"	12.5"	C07
18221	31.0/10.5-15	C	11.0"	30.8"	97.0"	10-12"	12"	14.7"	C07
18235	31.5/12.5-15 W*	C	13.5"	31.7"	99.5"	12-14"	14"	17.2"	D05
18237	13.5/31.5-15 L***	C	13.5"	31.7"	99.5"	12-14"	14"	17.2"	C07
18239	31.5/13.5R-15 Radial	C	13.5"	31.8"	99.7"	14-15"	14"	16.9"	C06
18240	31.0/14.0-15	C	14.0"	31.2"	98.0"	12-14"	12"	16.5"	D05
18242	32.0/12.0-15	C	12.2"	32.0"	101.0"	10-12"	12"	15.8"	D05
18243	32.0/13.0-15	C	13.2"	32.0"	101.0"	12-13"	12"	16.5"	D05
18245	32.0/13.5-15 W*	C	14.0"	32.3"	102.0"	12-14"	14"	17.7"	D05
18247	32.0/13.5R-15 Radial	C	13.5"	32.2"	101.2"	14-15"	14"	17.0"	C06
18250	32.0/14.0-15	C	14.0"	32.3"	102.0"	12-14"	14"	17.7"	D05
18255	14.0/32.0-15 L***	C	14.0"	32.3"	102.0"	12-14"	14"	17.8"	C07
18260	32.0/14.5-15 W*	C	15.0"	32.6"	102.5"	14-15"	14"	18.4"	D05
18265	14.5/32.0-15 L***	C	15.0"	32.3"	102.0"	14-15"	14"	18.4"	C07
18267	32.0/14.5R-15 Radial	C	15.0"	32.2"	101.2"	14-16"	14"	18.1"	C06
18280	32.0/17.0-15	C	17.2"	32.3"	102.0"	15-16"	16"	20.7"	D06
18300	32.5/16.5-15	C	16.7"	32.3"	101.5"	15-16"	15"	19.8"	C07
18331	33.0/10.5-15	C	11.5"	33.0"	104.0"	10-12"	12"	15.6"	C11
18335	10.5/33.0-16	C	11.5"	33.4"	105.0"	14-16"	15"	17.3"	C11
18350	33.0/12.0-15	C	12.2"	33.0"	102.0"	10-12"	10"	15.2"	C09
18361	33.0/14.5R-15 Radial	C	15.0"	33.0"	104.0"	14-16"	14"	18.4"	C06
18367	14.5/33.0-15 L***	C	14.5"	33.0"	104.0"	14-15"	14"	18.2"	C07
18370	33.0/15.0-15	C	15.0"	33.0"	104.0"	14-15"	14"	18.7"	D05

SOFT	JR3	C06 C07	C11	Drag Front	FIRM
	D05	D06	D07 N/TF C09		

* STIFF SIDEWALL
 ** SOFT SIDEWALL
 *** LIGHTWEIGHT

DRAG RACING CONT.

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
18400	33.0/16.0-15	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D05, D06, C07
18450	33.0/16.5-15 S**	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	D06, C07
18500	33.0/17.0-16	C	17.0"	33.0"	104.0"	15-16"	15"	19.8"	C07
18600	33.5/16.0-15	C	17.0"	33.6"	106.0"	15-16"	15"	19.8"	C07
18640	33.5/16.5-16 S**	C	17.0"	33.6"	106.0"	15-16"	16"	19.9"	C07
18650	33.5/17.0-16	C	17.0"	33.6"	106.0"	15-16"	16"	19.9"	C07
18700	33.5/17.0-16	C	17.0"	33.6"	106.0"	15-16"	16"	20.7"	C06
18750	33.5/17.0-16	C	17.0"	33.5"	105.0"	15-16"	16"	19.9"	PS1
18780	17.0/34.5-16	C	17.0"	35.0"	110.0"	15-16"	16"	20.5"	C2055
18790	34.5/17.0-16	C	17.0"	35.0"	110.0"	15-16"	16"	21.4"	C2055
18800	34.5/17.0-16	C	17.0"	35.0"	110.0"	15-16"	16"	21.4"	C4000
18905	36.0/17.0-16	C	17.7"	36.2"	114.0"	15-16"	16"	21.5"	C2055
18975	12.00-16	C	12.0"	33.0"	105.0"	10-12"	12"	16.2"	N/TF

SOFT	JR3	C06 C07	C11	Drag Front	FIRM
	D05	D06	D07	N/TF C09	

* STIFF SIDEWALL
 ** SOFT SIDEWALL
 *** LIGHTWEIGHT

DRAG RACING

ROAD RACING SLICKS – BIAS

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
43101	18.0 X 6.0-10	C2000 F500	6.2"	18.1"	57.0"	6"	6"	8.1"	R25B, R35A
43105	18.0 X 7.5-10	F500	7.5"	18.3"	57.5"	7-8"	8"	9.5"	R25B, R35A
43110	19.5 X 6.5-10	F500	6.5"	19.4"	61.0"	6"	6"	8.2"	R25B
43120	19.5 X 7.5-10	F500	7.5"	19.5"	61.2"	7-8"	8"	9.5"	R25B
43128	20.5 X 6.0-13	C2000 FF	6.0"	21.0"	66.0"	5.5"	5.5"	7.0"	R25B, R35A
43130	20.0 X 6.0-13	CF	6.0"	20.7"	65.0"	5.5-6.5"	5.5"	7.0"	R60A
43162	20.5 X 7.0-13	C2500 FC, FM, S2000, DSR	6.75"	20.8"	66.2"	6-8"	6"	8.0"	R25B, R35A, R45B
43169	20.0 X 7.5-13	C2500 CSR, DSR	8.0"	20.6"	65.0"	6-9"	8"	9.4"	R25B, R35A
43170	20.0 X 8.0-13	FP, GP, HP, GT4, GT5	8.0"	20.0"	63.0"	5-6"	6"	9.2"	R25B, R35A, R45B
43185	20.0 X 9.0-13	C2500 FA, CSR, DSR	9.75"	20.6"	64.7"	8-10"	10"	11.0"	R25B, R35A
43190	20.0 X 9.5-13	GT4	9.4"	20.0"	63.0"	7"	7"	10.5"	R25B, R35A, R45B
43240	21.0 X 9.5-13	GT3, GT4	9.5"	21.0"	66.0"	7"	7"	10.5"	R60A
43270	21.5 X 8.0-13	SCCA-F, SR	8.2"	21.4"	66.8"	8"	8"	9.5"	R45B
43275	21.5 X 8.0-13	C3000 PRO F/M	8.2"	21.5"	67.5"	8-10"	8"	9.5"	R35A, R45A
43289	22.0 X 8.0-13	C2500 FA, FC, FM, S2000, DSR	8.1"	22.1"	69.2"	8-10"	8"	9.5"	R25B, R35A, R45B
43293	22.0 X 9.0-13	C2500 FA, FC, FM, S2000, DSR	8.8"	22.0"	69.5"	8-10"	8"	10.0"	R25B, R35A, R45B
43301	22.0 X 10.0-13	SCCA-F, SR	9.8"	22.3"	70.0"	10"	10"	11.0"	R45B
43306	22.5 X 7.2-13	C2000 FF	7.25"	22.6"	71.0"	5.5"	5.5"	9.8"	R25B, R35A
43307	22.5 X 7.2-13	CF	7.25"	22.6"	71.0"	5.5"	5.5"	9.8"	R60A
43308	22.5 X 9.0-13	C2500 FM	9.0"	22.6"	71.0"	8-10"	10"	10.1"	R25B, R35A, R45B
43310	22.5 X 10.0-13	C2500 CSR, DSR	9.8"	22.6"	71.0"	8-10"	10"	11.0"	R25B, R35A
43318	23.0 X 12.0-13	C3000 FA, CSR	12.0"	23.6"	74.1"	12-15"	15"	15.9"	R25B, R35A
43335	21.0 X 5.0-15	FV	5.0"	21.2"	66.5"	4"	4"	5.5"	R45B, R55A
43340	21.5 X 5.5-15	FV	5.5"	21.4"	67.0"	4"	4"	6.0"	R45B, R55A
43351	22.5 X 5.5-15	FV	5.5"	21.9"	69.0"	4"	4"	6.5"	R45B, R55A
43361	22.5 X 9.5-15	C3000 FA	9.2"	22.9"	72.0"	10"	10"	10.7"	R35A
43375	23.0 X 8.5-15	EP	8.2"	22.8"	71.5"	6-7"	7"	9.4"	R35A, R45B, R55A

SOFT	R25B	R35A	R45B	R55A	FIRM
					R60A

ROAD RACING SLICKS

ROAD RACING SLICKS – BIAS CONT.

ROAD RACING SLICKS

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
43385	23.0 X 9.5-15	EP, GT3	9.2"	22.8"	71.5"	6-7"	7"	10.4"	R35A, R45B, R55A
43390	24.0 X 11.0-15	CAN AM	11.0"	23.8"	75.0"	10"	10"	12.0"	R45B
43460	27.0 X 15.0-15	CAN AM	14.8"	27.0"	85.0"	16"	16"	17.7"	R45B
43470	22.0 X 10.0-16	GT2	9.7"	22.9"	72.0"	10-11"	10"	10.7"	R35A, R45B
43480	23.5 X 11.5-16	GT2	11.0"	23.8"	75.0"	10-12"	12"	12.5"	R35A, R45B
43492	25.0 X 12.0-16	GT1, GT2	12.0"	25.3"	79.5"	10-12"	12"	12.7"	R35A, R45B
43497	25.0 X 13.0-16	GT1, GT2	13.0"	25.3"	79.5"	12"	12"	13.5"	R45B
43535	27.0 X 14.0-16	C4000 GT1	13.8"	26.7"	84.0"	12-13"	12"	14.5"	R35A, R45B

ALL TREAD PATTERNS cc

SOFT _____ R25B _____ R35A _____ R45B _____ R55A _____ R60A _____ FIRM

ROAD RACING SLICKS – RADIAL

ROAD RACING SLICKS

ITEM NUMBER	TIRE SIZE	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	COMPOUNDS
43540	20.5 X 7.0R-13	F2000	7.125"	21.0"	66.0"	6"	6"	8.375"	
43545	22.5 X 9.0R-13	F2000	9.125"	22.6"	71.0"	8"	8"	9.875"	
43550	23.0 X 9.5R-13	FA	9.6"	23.0"	72.25"	10"	10"	11.0"	R25B
43565	23.5 X 13.0R-13	FA	12.8"	23.5"	73.8"	14-15"	15"	15.1"	R25B
43570	23.0 X 9.5R-15	FA	9.4"	22.9"	72.0"	10"	10"	10.7"	R25B, R35A
43585	23.5 X 13.0R-15	FA	13.0"	23.5"	73.8"	14"	14"	14.5"	R25B, R35A
43590	27.5 X 11.5R-15	HSCF	11.5"	27.4"	86.0"	10"	9.5"	12.81"	
43595	27.5 X 11.5R-15	HSCR	11.5"	27.4"	86.0"	10"	9.5"	12.81"	
43655	23.5 X 11.0R-16	GT2	10.6"	23.6"	74.0"	10"	10"	11.0"	R25B, R35A
43660	23.5 X 12.0R-16	GT2	12.0"	23.5"	73.8"	12"	12"	13.0"	R25B, R35A
43665	25.5 X 12.0R-16	GT2	12.4"	25.6"	80.5"	12"	12"	13.5"	R35A
43671	25.5 X 12.5R-16	C2000 GT1	12.4"	25.8"	81.0"	12"	12"	13.3"	R35A
43676	25.5 X 14.0R-16	C2000 GT1	13.6"	25.7"	80.9"	12"	12"	14.1"	R25B, R35A, R45B
43681	27.0 X 13.0R-16	C2000 GT1	13.0"	27.3"	85.8"	13"	13"	14.6"	R35A
43691	28.0 X 14.0R-16	C2000 GT1	13.9"	28.2"	88.5"	13"	13"	15.1"	R25B, R35A, R45B
43825	250/650R18		9.125"	25.604"	80.4"	8-9.5"	9"	9.875"	R100
43835	265/645R18		10.125"	25.48"	80.06"	9-10"	10"	10.875"	R80, R100
43840	280/680R18		10.0"	26.9"	84.6"	9-11"	10"	11.25"	R100
43855	285/645R18		10.9"	25.5"	80.0"	10-12"	11"	11.7"	R80, R100
43860	305/30R18 VRL		11.6"	25.6"	80.5"	11-12"	11"	12.5"	
43865	305/645R18		11.75"	25.64"	80.6"	11-13"	12"	12.68"	R80, R100
43870	320/650R18		12"	25.70"	80.75"	11-12"	12"	13"	R100
43875	315/690R18		12.25"	27.25"	85.62"	11-12"	12"	13.5"	R100
43880	335/30R18 VRL		12.6"	25.6"	80.5"	12-13"	12"	13.5"	
43890	310/710R18		12.437"	28.13"	88.37"	10-12"	12"	13.56"	R100

ALL TREAD PATTERNS cc

SOFT _____ R25B _____ R35A _____ R45B _____ FIRM

ROAD RACING WETS – BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERNS	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH
44125	19.5 X 6.5-10	I	F500	6.2"	19.7"	62.0"	6-8"	8"	8.2"
44140	20.0 X 6.5-13	I	FF, FM, FC, S2000, DSR	6.2"	20.7"	65.0"	6-7.5"	6"	7.0"
44150	20.0 X 7.5-13	I	CSR, FA	7.4"	20.6"	64.6"	7-8"	7"	8.3"
44165	20.0 X 8.0-13	I	FP, GP, HP, GT4, GT5	8.0"	20.5"	64.5"	6"	6"	8.8"
44185	21.0 X 6.5-13	I	FF, FM, FC, S2000, DSR	6.7"	21.2"	66.5"	6-8"	6"	7.2"
44195	21.5 X 7.5-13	I	SCCA-F, SR	7.5"	21.4"	66.8"	8.0"	8"	8.8"
44217	22.0 X 9.0-13	I	SCCA-F, SR, FC, FA, FM, S2000, DSR, CSR	8.5"	22.9"	71.8"	8.5-10"	8"	10.0"
44220	22.5 X 7.5-13	I	FF	7.5"	22.8"	71.5"	5.5-6.0"	5.5"	9.8"
44266	22.5 X 5.0-15	I	FV	5.0"	22.0"	69.2"	4"	4"	6.5"
44275	22.5 X 9.0-15	I	FA	8.8"	22.4"	70.5"	10"	10"	10.1"
44277	23.0 X 9.0-15	I	EP, GT3	8.5"	22.4"	70.5"	6-7"	7"	10.0"
44280	23.5 X 11.5-15	I	FA	11.5"	23.7"	74.5"	14"	14"	14.8"
44307	27.0 X 10.0-15	I	HSC/GTA	10.0"	27.0"	84.0"	10-11"	10"	12.5"

ROAD RACING WETS – RADIAL

ITEM NUMBER	TIRE SIZE	TREAD PATTERNS	APPLICATION	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH
44440	20.5 X 7.0R-13 WET	I	F2000, FC	7.1"	21.0"	66.0"	6"	6"	8.3"
44445	22.5 X 9.0R-13 WET	I	F2000, FC	9.1"	22.6"	71.0"	8"	8"	9.8"
44450	23.0 X 9.5R-13	I	FA	9.5"	23.0"	72.4"	10"	10"	10.6"
44460	23.5 X 12.0R-13	I	FA	11.9"	23.5"	73.8"	14"	13"	14.0"
44590	23.0 X 9.5R-15	I	FA	9.5"	23.0"	72.4"	10"	10"	10.6"
44595	23.5 X 12.0R-15	I	FA	11.9"	23.5"	73.8"	14"	14"	14.0"
44655	23.5 X 11.0R-16	I	GT2	10.6"	23.6"	74.0"	10"	10"	11.0"
44671	25.5 X 12.5R-16	I	GT1, GT2	12.2"	25.7"	80.9"	12"	12"	13.2"
44681	27.0 X 13.0R-16	I	GT1	13.6"	27.3"	85.7"	12"	12"	14.2"

TREAD PATTERN IS HAND GROOVED.

SPORTS CAR D.O.T. - BIAS

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	STREET T.D.	WET
45100	P185/60D-13	H	6.2"	20.6"	64.7"	5-7"	5"	7.0"	X	
45110	P205/60D-13	H	6.2"	22.4"	70.5"	5.5-7"	5.5"	7.5"	X	
45111DS	P205/60D-13*	L	6.8"	21.9"	68.8"	5.5-7.5"	5.5"	7.8"		X
45115	P225/45D-13	H	7.8"	20.8"	65.5"	6.5-8.5"	7.5"	9.0"	X	
45120	P205/60D-14	H	7.2"	23.0"	72.3"	6-8"	5.5"	8.3"	X	
45140	P225/50D-14	H	7.8"	23.0"	72.5"	7-9"	6"	8.8"	X	
45160	P225/45D-15	H	7.6"	23.0"	72.5"	6.5-8.5"	7.5"	8.5"	X	
45170	P225/50D-15	H	7.0"	24.0"	75.5"	6.5-8.5"	6"	8.5"	X	
45180	P225/60D-15	H	8.0"	25.8"	81.0"	7-9"	6"	9.2"	X	
45165	P245/45D-15	H	8.5"	24.0"	75.5"	7.5-9.5"	8"	10.0"	X	
45190	P245/60D-15	H	8.0"	26.4"	83.0"	7-9.5"	7"	10.0"	X	
45200	P275/60D-15	H	9.5"	27.6"	86.5"	8.5-10"	7.5"	11.0"	X	

*DS RECOMMENDED FOR WET APPLICATION ONLY.

VINTAGE & HISTORIC

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	MODEL
44390	165/70-10	H	5.2"	18.8"	59.0"	5-6"	5.5"	7.3"	HOOSIER T.D.
45105	A70-13	H	6.2"	22.4"	70.3"	5-7"	5"	7.5"	STREET T.D.
44285	25.5 X 8.5-15	H	8.7"	25.4"	79.7"	8-10"	8"	10.3"	HOOSIER T.D.
44295	25.5 X 10.0-15	H	10.0"	25.8"	81.0"	8-11"	8"	11.2"	HOOSIER T.D.
44301	26.5 X 7.0-15	H	7.0"	26.4"	83.0"	6"	6"	9.1"	HOOSIER T.D.
44305	26.5 X 9.5-15	H	9.5"	26.6"	83.5"	8-10"	8"	11.0"	HOOSIER T.D.
44315	27.5 X 11.0-15	H	11.0"	27.7"	87.0"	10-13"	10"	13.2"	HOOSIER T.D.
44335	24.0 X 8.5-16	H	8.2"	24.1"	75.4"	8-10"	8"	10.5"	HOOSIER T.D.
44345	25.5 X 10.0-16	H	10.0"	25.6"	80.5"	9-11"	9"	11.3"	HOOSIER T.D.
44400	5.00-15	L	5.2"	24.7"	77.6"	4-6"	4"	7.0"	VINTAGE T.D.
44405	120/590-15	L	4.8"	22.6"	70.9"	4.5"	4.5"	6.1"	VINTAGE T.D.
44408	135/620-15	L	5.6"	24.1"	75.6"	4.5"	4.5"	6.9"	VINTAGE T.D.
44410	5.50-15	L	6.5"	24.7"	77.6"	4.5-7"	4.5"	7.7"	VINTAGE T.D.
46006	P185/70R14	G	6.8"	24.1"	75.8"	4.5-6"	6"	7.75"	SPEEDSTER
46008	P205/65R14	G	7.5"	24.1"	75.8"	5.5-8"	6"	8.25"	SPEEDSTER
46010	P185/65R15	G	6.4"	24.2"	76.0"	5.0-6.5"	5"	7.0"	SPEEDSTER
46015	P205/60R15	G	7.3"	24.2"	76.0"	5.5-7.5"	6.5"	8.25"	SPEEDSTER

NOTE: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

SPORTS CAR D.O.T. - RADIAL

ITEM NUMBER	TIRE SIZE	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	A6 AUTO CROSS	R6 ROAD RACE
46300	P185/60ZR13	E	6.9"	21.7"	68.2"	6-7"	6.0"	7.8"		X
46305	P205/60ZR13	E	8.0"	22.8"	71.7"	5.5-7.5"	6.0"	8.8"		X
46307	P225/45ZR13	E	8.5"	20.9"	65.8"	7.0-8.5"	7.5"	9.3"	X	X
46310	P225/50ZR13	E	8.5"	21.9"	69.0"	6-8"	7.0"	9.4"	X	X
46320	P255/40ZR13	E	9.5"	20.9"	65.6"	8.5-10"	9.0"	10.5"	X	
46405	P205/55ZR14	E	8.1"	22.8"	71.6"	5.5-7.5"	7.0"	9.1"	X	X
46410	P205/60ZR14	E	7.8"	23.6"	74.2"	7-8"	6.0"	8.2"		X
46415	P225/50ZR14	E	8.5"	22.9"	72.0"	6-8"	7.0"	9.4"	X	X
46500	P205/50ZR15	E	8.0"	22.8"	71.7"	5.5-7.5"	6.5"	8.7"	X	X
46500	P205/50ZR15 SM6	E	8.0"	22.8"	71.7"	5.5-7.5"	6.5"	8.7"		X
46505	P215/60ZR15	E	8.3"	25.2"	79.1"	6.0-7.5"	7.0"	9.2"		X
46510	P225/45ZR15	E	9.0"	22.9"	72.0"	7.0-8.5"	7.5"	9.8"	X	X
46515	P225/50ZR15	E	8.8"	23.8"	74.8"	6-8"	7.0"	9.8"	X	X
46520	P225/55ZR15	E	8.7"	24.8"	78.0"	6-8"	7.0"	9.6"		X
46525	P245/50ZR15	E	9.2"	24.8"	78.0"	7.0-8.5"	7.5"	10.1"		X
46535	P275/35ZR15	E	10.1"	23.0"	72.2"	9.0-11.0"	9.5"	10.8"	X	X
46540	P275/50ZR15	E	10.0"	25.5"	80.0"	7.5-9.5"	8.0"	10.8"		X
46600	P205/45ZR16	E	8.0"	22.8"	71.7"	6.5-7.5"	7.0"	8.7"	X	X
46610	P225/50ZR16	E	9.0"	24.7"	77.6"	6-8"	7.0"	9.5"	X	X
46615	P245/45ZR16	E	9.2"	24.7"	77.7"	7.5-9.0"	8.0"	10.1"	X	X
46620	P255/50ZR16	E	9.4"	26.2"	82.2"	7-9"	8.0"	10.5"	X	X
46630	P275/45ZR16	E	10.3"	25.6"	80.5"	8.5-10.0"	9.0"	11.2"	X	X
46700	P205/40ZR17	E	7.0"	23.8"	74.8"	7-8"	8.0"	8.5"		X
46705	P225/40ZR17	E	8.9"	23.8"	74.5"	7-9"	7.5"	9.8"	X	X
46710	P225/45ZR17	E	8.8"	24.7"	77.7"	7.0-8.5"	7.5"	9.7"	X	X
46715	P245/40ZR17	E	9.3"	24.5"	77.0"	8.0-9.5"	8.5"	10.0"	X	X
46720	P245/45ZR17	E	9.4"	25.7"	80.7"	7.5-9.0"	8.0"	9.9"		X
46725	P255/45ZR17	E	9.7"	26.2"	82.2"	8.0-9.5"	9.0"	10.8"	X	X
46730	P275/40ZR17	E	10.3"	25.5"	80.1"	9.0-11.0"	9.5"	11.0"	X	X
46733	P295/35ZR17	E	10.8"	25.3"	79.5"	9.5-11.0"	10.0"	11.6"	X	X
46735	P315/35ZR17	E	11.4"	25.6"	80.4"	11-12"	11.0"	12.6"	X	X
46740	P335/35ZR17	E	12.9"	25.6"	80.5"	11-13"	12.0"	13.6"	X	X
46810	P225/40ZR18	E	8.8"	24.8"	77.8"	7.5-9.0"	8.0"	9.5"	X	X
46820	P245/35ZR18	E	9.1"	24.7"	77.7"	8.0-9.5"	8.5"	9.8"	X	X
46825	P245/40ZR18	E	9.3"	25.7"	80.6"	8.0-9.5"	8.5"	10.5"	X	X
46830	P255/40ZR18	E	9.8"	26.2"	82.1"	8.5-10.0"	9.0"	10.6"		X
46832	P255/35ZR18	E	10.3"	24.8"	77.8"	8.5-10.0"	9.0"	10.8"	X	X
46836	P275/35ZR18	E	10.3"	25.5"	80.2"	9-11"	9.5"	10.7"	X	X
46840	P285/30ZR18	E	10.9"	24.9"	78.1"	10-11"	10.0"	11.5"	X	X
46843	P295/30ZR18	E	10.8"	25.3"	79.5"	9.5-11"	10.0"	11.6"	X	X
46846	P315/30ZR18	E	11.8"	25.6"	80.5"	11-12"	11.0"	12.5"	X	X
46850	P335/30ZR18	E	12.8"	25.6"	80.5"	12-13"	12.0"	13.5"	X	X
46855	P345/35ZR18	E	13.2"	26.8"	84.2"	11-13"	12.0"	13.9"	X	X
46915	P235/35ZR19	E	9.25"	25.6"	80.5"	8.0-9.5"	9.0"	10.2"	X	X
46925	P265/35ZR19	E	9.6"	26.2"	82.25"	9-10"	9.0"	10.4"	X	X
46935	P295/30ZR19	E	10.4"	26.1"	82.1"	10-12"	10.0"	11.5"	X	X
46937	P315/30ZR19	E	12.0"	26.1"	82.2"	11-12"	11.0"	12.5"	X	X
46940	P315/40ZR19	E	11.3"	28.9"	90.7"	11-12"	11.0"	12.9"		X
46945	P325/30ZR19	E	12.2"	26.8"	84.1"	12-13"	13.0"	13.6"	X	X
46950	P345/30ZR19	E	13.0"	26.8"	84.3"	12-13"	13.0"	14.1"	X	X

NOTE: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

SPORTS CAR D.O.T. RADIAL WET

ITEM NUMBER	TIRE SIZE	SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH
46105	P205/60R13	86H	J	7.1"	23.5"	73.8"	6-7.5"	6.0"	8.5"
46115	P205/55R14	85H	J	7.1"	23.5"	73.8"	6.5-7.5"	6.5"	8.7"
46125	P205/50R15	84H	J	7.1"	23.5"	73.8"	6.5-7.5"	6.5"	8.2"
46130	P225/55R15	92H	J	8.8"	24.8"	77.9"	7-8"	7.0"	9.4"
46135	P205/45R16	77H	J	7.1"	23.5"	73.8"	7-7.5"	7.0"	8.4"
46140	P225/50R16	91H	J	8.8"	24.8"	77.9"	7-9"	7.0"	9.6"
46145	P245/45R16	88H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10"
46150	P255/50R16	99H	J	9.3"	26.3"	82.5"	8-9"	8.0"	10.7"
46170	P225/45R17	84H	J	8.8"	24.8"	77.9"	8-9"	7.5"	9.5"
46175	P245/40R17	86H	J	9.0"	24.8"	77.9"	7-9"	8.0"	10"
46177	P245/45R17	89H	J	9.0"	25.5"	80.1"	7-9"	8.0"	10"
46185	P275/40R17	93H	J	10.0"	25.2"	79.2"	9-11"	9.5"	11.3"
46190	P315/35R17	93H	J	11.8"	25.6"	80.4"	11-12"	11"	12.7"
46200	P225/40R18	83H	J	8.8"	24.8"	77.9"	7-9"	8"	9.9"
46205	P245/35R18	80H	J	9.0"	24.8"	77.9"	7-9"	8"	10"
46207	P245/40R18	88H	J	8.75"	25.5"	80.25"	8-9.5"	9.0"	9.75"
46210	P255/40R18	90H	J	9.3"	26.3"	83.0"	9-10"	9.0"	10.5"
46215	P275/35R18	87H	J	10.0"	25.2"	79.2"	10-11"	9.5"	11.3"
46220	P305/30R18	89H	J	11.8"	25.6"	80.4"	11-12"	11"	12.7"

NOTE: H Speed Rating = 130 mph/210 km/h.

NOTE: DOT labeled Hoosier Racing Tires meet Department of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

PRO STREET D.O.T. RADIAL

ITEM NUMBER	TIRE SIZE	SPEED RATING	TREAD PATTERN	TREAD WIDTH	APPROX. DIA.	APPROX. CIRC.	RECOM. RIM	MEASURED RIM	SECTION WIDTH	MAX. LOAD	RATED INF. PSI	MODEL
Fronts												
19030	24 X 7.50R-15 LT	71H	bb	5.3"	23.8"	73.3"	5-6.5"	6"	7.5"	760	35	Pro Street
19040	25 X 7.50R-15 LT	75H	bb	5.3"	24.9"	76.9"	5-6.5"	6"	7.5"	855	35	Pro Street
19050	26 X 7.50R-15 LT	79H	bb	5.3"	25.9"	80.5"	5-6.5"	6"	7.5"	965	35	Pro Street
19055	26 X 7.50R-17 LT	74H	bb	5.3"	25.9"	80.5"	5-6.5"	6"	7.5"	825	35	Pro Street
19075	27 X 10.50R-15 LT	88H	bb	8.3"	26.5"	82.8"	7-9.0"	8.5"	10.5"	1235	35	Pro Street
19100	28 X 9.50R-15 LT	90H	bb	8.0"	27.0"	85.0"	7.5-9.0"	8.0"	9.75"	1325	35	Pro Street
19150	29 X 12.50R-15 LT	89H	bb	10.0"	29.0"	90.8"	8.5-11"	10"	13.0	1280	25	Pro Street
19200	29 X 15.50R-15 LT	91H	bb	12.1"	29.0"	91.5"	11-13"	12"	15.2"	1355	25	Pro Street
19215	29 X 15.50R-16 LT	89H	bb	12.1"	29.0"	91.8"	11-13"	12"	15.2"	1280	25	Pro Street
19250	29 X 18.50R-15 LT	93H	bb	14.6"	29.0"	91.3"	13-16"	14"	17.8"	1435	25	Pro Street
19275	31 X 12.50R-15LT	95H	bb	10.3"	31.0"	96.5"	8.5-11"	10"	13.4"	1520	25	Pro Street
19276	31 X 12.50R-16 LT	93H	bb	10.3"	31.0"	96.5"	8.5-11"	10"	12.8"	1435	25	Pro Street
19300	31 X 16.50R-15 LT	98H	bb	12.8"	31.0"	96.3"	12-14"	12"	16.0"	1655	25	Pro Street
19315	31 X 16.50R-16 LT	96H	bb	12.8"	31.0"	96.8"	12-14"	12"	16.0"	1565	25	Pro Street
19325	31 X 16.50R-17 LT	94H	bb	12.8"	31.0"	96.8"	12-14"	12"	16.0"	1475	25	Pro Street
19350	31 X 18.50R-15 LT	99H	bb	14.5"	31.0"	96.3"	13-16"	14"	18.0"	1710	25	Pro Street
19375	31 X 18.50R-17 LT	95H	bb	14.5"	31.0"	96.3"	13-16"	14"	18.0"	1520	25	Pro Street
19410	33 X 21.50R-15 LT	107H	bb	16.8"	32.0"	100.8"	15-19"	17"	21.3"	2150	25	Pro Street

"Pro Street Tires are designed for highway use and are not suitable for racing purposes."

NOTE: H Speed Rating = 130 mph / 210 km/h

NO WARRANTY POLICY

Hoosier Racing Tire Corp. offers racing tires for sale only upon the conditions and the terms contained in this disclaimer of liability and indemnity. Due to many varied and different conditions which Hoosier Racing Tires and Tubes are exposed and because of the manner in which racing is conducted, Hoosier Racing Tire Corp. makes absolutely **no warranty**, expressed or implied, as to the fitness for a general or particular purpose or of merchantability in connection with any offer of sale of Hoosier Racing Tires and tubes. **“HOOSIER RACING TIRES AND TUBES ARE SOLD AS IS.”** Race tires are not tested or labeled to meet FMVSS 109, 119, 139 or ECE36 Safety Standards. Therefore it is dangerous and illegal to sell race tires for use on public highways. Any person selling Hoosier Racing Tires or Tubes for highway use agrees to indemnify and reimburse Hoosier Racing Tire Corp. for all loss, damage, or liability Hoosier Racing Tire Corp. may suffer because of such sales. Not applicable where prohibited by law. Not following these warnings **CAN CAUSE SEVERE INJURY OR DEATH**. For more information read tire labels, follow manufacturer’s warnings as molded in tire sidewalls and visit hoosiertire.com.

WARNING

When seating beads never exceed maximum bead seating pressure as molded in tire sidewall. Never exceed manufacturer’s maximum inflation pressure.

WARNING

NOT FOR HIGHWAY USE: All Hoosier Racing Tires including DOT labeled Hoosier Racing Tires are designed for racing purposes only on specified racing surfaces and are **not to be operated on public roadways**. DOT labeled Hoosier Racing Tires meet Department Of Transportation requirements for marking and performance only and are **NOT INTENDED FOR HIGHWAY USE**. It is unsafe to operate any Hoosier Racing Tire including DOT tires on public roads. The prohibited use of Hoosier Racing Tires on public roadways may result in loss of traction, unexpected loss of vehicle control, or sudden loss of tire pressure, resulting in a vehicle crash and possible injury or death.

Exception – “PRO STREET” page 19.

WARNING

Service Life for Race Tires: Old tires can fail in use, causing loss of vehicle control and personal injury. Environmental conditions like temperature extremes, exposure to sunlight, electric arc, solvents, automotive fluids, and atmospheric pollutants accelerate the aging process. Hoosier Racing Tire strongly recommends that new (sticker) tires should be put in service within 2 years of date of purchase. Used (scuffed) tires have a shorter service life than new (sticker) tires. Poor storage and infrequent use accelerate the aging process.

WARNING

Chemical Treatment of Tires: Hoosier Racing Tires strictly forbids any chemical alteration of the tire carcass and/or tread compound, such as tire “soaking” or use of tread “softener.” Hoosier Racing Tire strictly forbids the physical defacement (removal, altering or covering), of tire sidewall markings in any manner. Failure to comply with this warning could result in premature or catastrophic tire failure and may result in serious injury or death.

WARNING

Application/Misuse: All Hoosier Racing Tire products are designed for a specific purpose. Consult with Hoosier Racing Tire Corp. for specific fitment and application. Utilizing Hoosier Tires in any form outside of their intended use constitutes **misuse** of the product and can **cause severe injury or death**. Hoosier Racing Tire products are designed and manufactured for racing purposes only, within a closed course designed for organized competition. Not for recreational use. Hoosier Tires should never be used for Land Speed Record vehicles including Jet/Rocket cars.

FREEZE WARNING

Freeze Crack Advisory: This advisory addresses proper storage and use of Hoosier tires in cold conditions. Hoosier Tires, especially asphalt and hard compound tires, may experience Rubber Cracking if the tires are transported, crushed, flexed or stressed when frozen. The following guidelines are provided to avoid this problem.

1. Always store Hoosier Racing Tires indoors at temperatures above 32° F.
2. If tires have been subject to 32°F or less, allow them to warm to room temperature (about 70°F) for a minimum of 24 hrs before the tire is mounted, transported or flexed.
3. Always use spare tires not intended for future competition to store vehicles for prolonged periods of time or winter transport.
4. If below freezing temperatures are expected, please consider shipping tires once more favorable conditions exist.

Do not use tires that have evidence of Freeze Crack Damage.

WARNING

Verify Correct Wheel and Bead Flange: All tires are designed to be used on wheels that are manufactured to Tire and Rim Association (T&RA) specifications and tolerances. Some rims are non-standard or damaged and it is necessary to inspect the rim flange to assure proper fit. Consult your specific rim manufacturer to determine if your rim can be used in this application. Never attempt to install and inflate a tire of one bead diameter on a rim or wheel of a different bead diameter. Use of Hoosier Racing Tires on wheels with incorrect bead flanges or wheels that do not meet T&RA standards can cause the assembly to fail and burst with explosive force sufficient to cause serious personal injury or death.

WARNING

Special Tire Mounting Instructions: Tire changing should be done only by trained personnel using proper tools and procedures. Failure to follow safe mounting procedures could cause faulty positioning of the tire and cause the assembly to burst with explosive force sufficient to cause serious injury or death. Always inspect tire for kinked beads or other possible damage that may have occurred in shipping or storage. Clean rim and lubricate beads with rubber lubricant. Always lock rim on mounting machine or place in safety cage. Use a clip on chuck, an in-line valve with a pressure gauge or adjustable regulator and remote inflation/deflation device. Have enough air hose to stay out of the trajectory. Stand back. (Refer to page 15).

DIRECTION OF ROTATION/MOUNTING INSTRUCTIONS

All Hoosier tires having directional arrows must be mounted so that the tire travels in the direction of the arrow. Hoosier tires having directional arrows will have them on both sidewalls. Directional arrows may not be on a tire that can have both left and/or right side application. All Hoosier tires not having directional arrows should be mounted as detailed below.

Every Hoosier race tire has a four character serial code embossed into ONE sidewall of the tire. All Hoosier DOT tires will also have two additional codes as required by the Department of Transportation. (Example: J7AB 4AX8 3701)

MOUNTING GUIDELINES FOR TIRES WITHOUT DIRECTIONAL ARROWS

CIRCLE TRACK RACING TIRES:

(Includes both dirt and asphalt tires)

Hoosier tires must be mounted with the **serial code** located toward the infield.

ROAD RACING TIRES:

(Includes catalog numbers beginning with 43, 44, 45, 46)

In most cases, Hoosier tires used in Road Race applications should be mounted with the **serial code** toward the center of the vehicle. Once a tire has been run in the proper orientation it is acceptable to remount the tire in the opposite direction to even out the wear.

DRAG RACING TIRES, INCLUDING DOT DRAG TIRES:

(Includes catalog numbers beginning with 17, 18)

Hoosier drag tires can be mounted to rotate in either direction. Hoosier drag tires can also be flipped or reversed to provide even wear.

Hoosier[®]

RACING TIRE

CORPORATE 65465 U.S. 31 ♦ Lakeville, IN 46536 ♦ (574) 784-3152 ♦ Fax: (574) 784-2385 ♦ www.hoosiertire.com

YOUR HOOSIER TIRE DISTRIBUTOR

Hoosier

TIRE EAST

56-H Loomis Street ♦ Manchester, CT 06042
Phone: (860) 646-9646 ♦ Fax: (860) 646-2054
E-mail: hterace@aol.com

Hoosier

TIRE SOUTH

Asphalt
P.O. Box 537 ♦ Welcome, NC 27374
Phone: (336) 731-6100 ♦ Fax: (336) 731-6086
E-mail: hoosieraspl@lexcominc.net

Hoosier

TIRE MIDWEST

Springfield
3886 E. State Route 54 ♦ Springfield, IL 62707
Phone: (217) 522-1955 ♦ Fax: (217) 522-6097
E-mail: tari@racetires.com

Hoosier

TIRE MID-ATLANTIC

Baltimore
2931 Industrial Park Drive ♦ Finksburg, MD 21048
Phone: (410) 833-2061 ♦ Fax: (410) 833-5921
E-mail: htma@hoosiermidatlantic.com

Hoosier

TIRE SOUTHWEST

103 Gross Road, Bldg. A ♦ Mesquite, TX 75149
Phone: (972) 289-RACE (7223) ♦ Fax: (972) 289-8055
E-mail: tomlorenz@smileyracing.com

Hoosier

TIRE CANADA-NY

1733 Maryland Avenue
Niagara Falls, New York 14305
Phone: (716) 285-7502 ♦ Fax: (800) 285-1454
E-mail: usasales@bicknellracingproducts.com

Hoosier

TIRE AUSTRALIA

17 Blind Road ♦ Nelson NSW, Australia 2765
Phone: (61) 296791990 ♦ Fax: (61) 296791187
E-mail: mdimport@bigpond.net.au

Hoosier

TIRE SOUTH

Road & Drag ♦ P.O. Box 290 ♦ Louisville, TN 37777
Phone: (865) 984-3232 ♦ Fax: (865) 681-0775
E-mail: road&drag@hoosiertiresouth.com

Hoosier

TIRE SOUTH

Dirt Oval
504 Frank Diggs Road ♦ Clinton, TN 37717
Phone: (865) 457-9888 ♦ Fax: (865) 457-8033
E-mail: hoosiertiresouth@charterinternet.com

Hoosier

TIRE MIDWEST

Indianapolis
4155 North 1000 E., Suite A ♦ Brownsburg, IN 46112
Phone: (317) 858-1234 ♦ Fax: (317) 858-1307
E-mail: hoosiertireindy@yahoo.com

Hoosier

TIRE MID-ATLANTIC

Pittsburgh
205 West Water Street ♦ Saxonburg, PA 16056
Phone: (724) 360-8000 ♦ Fax: (724) 360-8044
E-mail: htma@zoominternet.net

Hoosier

TIRE KANSAS

3801 W. Pawnee, Suite 200 ♦ Wichita, KS 67213
Phone: (316) 945-4000 ♦ Fax: (316) 945-4003
E-mail: htk@smileyracing.com

Hoosier

TIRE WEST

2608 E. California ♦ Fresno, CA 93721
Phone: (559) 485-4612 ♦ Fax: (559) 485-4632
E-mail: racing@hoosiertirewest.com

Hoosier

TIRE SOUTH

Dirt Oval ♦ 155 West Walker Memorial Drive
Suite 400 ♦ Ball Ground, GA 30107
Phone: (770) 704-6131 ♦ Fax: (770) 704-6132
E-mail: hoosierdavid@bellsouth.net

Hoosier

TIRE MIDWEST

Plymouth
1801 Jim Neu Drive ♦ Plymouth, IN 46563
Phone: (574) 936-8344 ♦ Fax: (574) 936-1673
E-mail: hoosiertireply@netscape.net

Hoosier

TIRE OHIO VALLEY

1933 Staunton Turnpike ♦ Parkersburg, WV 26104
Phone: (304) 428-5000 ♦ Fax: (304) 485-8038
1-800-430-7223 ♦ E-mail: todd@poske.com

Hoosier

TIRE NORTH

21601 John Deere Lane ♦ Rogers, MN 55374
Phone: (763) 428-8780 ♦ Fax: (800) 555-8577
E-mail: htrance@aol.com

INTERNATIONAL

Hoosier

TIRE CANADA

117-119 Cushman Road
St. Catharines, Ontario, Canada L2M6S9
Phone: (905) 685-3184 ♦ Fax: (800) 891-0521
E-mail: brp@cogeco.net

Hoosier

TIRE WESTERN CANADA

5601-45 ST ♦ Leduc, Alberta, Canada T9E7B1
Phone: (780) 986-7223 ♦ Fax: (780) 986-5267
E-mail: tim@geeandgeeracing.com

Hoosier

TIRE NEW ZEALAND

32 William Pickering Drive
Albany, Auckland ♦ New Zealand
Phone: (09) 4151388 ♦ Fax: (09) 4150788
E-mail: 8@cardwells.co.nz

Hoosier

TIRE U.K.

P.O. Box 380 ♦ Horley Surrey, RH6 0WW
United Kingdom
Phone: +44 (0) 1293 863579 ♦ +44 (0) 1282 864721
Fax: +44 (0) 1293 863574
E-mail: andyhoosiertire@hotmail.com

In addition to Australia, Canada, New Zealand and the United Kingdom, Hoosier Racing Tire Corp. has locations in Italy, Guatemala, Norway, Puerto Rico, Singapore/Malaysia, South Africa, Sweden and the United Arab Emirates. Contact information for these locations can be found on www.hoosiertire.com.
To learn more about purchasing Hoosier tires in areas not listed, you can e-mail us at internationalsales@hoosiertire.com.

"TIRES DESIGNED FOR CHAMPIONS"[®]